

SiSiB[®] LR8280 LSR

INTRODUCTION

SiSiB® LR8280 is high strength type two-component liquid silicone rubber for injection molding process. High performance elastomeric parts could be got through Mixing A:B= 1:1.

KEY FEATURES

Highly transparency

Excellent process ability

High strength

20,30, 40, 50, 60, 70 durometer grades available

ROHS and FDA test passed

TYPICAL PHYSICAL PROPERTIES

Product	SiSiB® LR8280 LSR
Appearance	Transparent
Curing Condition	130°C×5min, A:B=1:1
Hardness (Shore A)	80+/-3
Tensile Strength (MPa)	Min. 6.0
Elongation (%)	Min. 80
Tear Strength (KN/m)	Min. 16.0
Tensile set(%)	Max. 8.0
Linear shrinkage(%)	2.2~2.9

APPLICATIONS

Swimming goggles

Keypads

Kitchenwares

Power Chemical IS09001 IS014001 certificated

Copyright© 2008 Power Chemical Corporation Ltd. SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia



SiSiB[®] LR8280 LSR

Parts

PACKING AND STORAGE

SiSiB® LR8280 is supplied in 20Kg can or 200Kg drum.

Store in a cool and dry place out of direct sunlight.

Notes

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.

Power Chemical IS09001 IS014001 certificated Copyright© 2008 Power Chemical Corporation Ltd. SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia